

Designed for the homeowner.

Designed and built with homeowners in mind, the FDR16 is just right for subcompact and compact tractors. With our tapered rear discharge area, foreign objects are discharged closer to the ground, plus you can mow close to objects with either side of the mower. The floating lower clevises allow the mower to cut evenly over uneven terrain.



The driveline storage hook keeps the driveline off the ground when not in use.



Stressproof® is a Registered Trademark of Niagara Lasalle Corporation
Kevlar® is a Registered Trademark of DuPont™

	FDR1648	FDR1660	FDR1672
Horsepower	15-30 HP		
Hitch	Cat. 1		
Working Width (cm)	48" (122)	60" (152)	72" (183)
Overall Width (cm)	51" (130)	63" (160)	75" (190)
Weight - lb (kg)	486 (220)	577 (262)	619 (281)
Mowing Height	3/4" - 3-1/4"	3/4" - 5-1/4"	
Deck Material Thickness	3/16"		
Blades 3 ea. Heat Treated Alloy Steel	1/4" x 2-1/2" x 16-7/8"	1/4" x 2-1/2" x 21"	1/4" x 2-1/2" x 25"
Blade Overlap	1-1/4"		
Blade Spindles	Greaseable		
Blade Tip Speed	16,203 FPM	18,195 FPM	18,130 FPM
Castered Gauge Wheels, 4-each	3-1/4" x 10" Solid Rubber Tire		
Castered Wheel Spindle	1" Diameter Stressproof® Material		
Drive Train	540 RPM B-Section V-Belt		
Driveline	Heavy-duty w/Quick Coupler		
Front Roller	Optional		

*See dealer for complete warranty information.

Color Options:    



60" & 72" Only



- Two position top hitch allows for various tractor lift capabilities
- Floating 3-point for ground following capabilities
- 1" Stressproof® wheel spindles with nylon bushings for smooth casting
- Single B-section belt with Kevlar®
- Grease bearings from top without removing belt covers
- Optional mulching blades available

